

CR4, Battery Pack Charger for d62 batteries

Features

- Charges batteries for d62
- Charges six batteries simultaneously
- Easy to wipe clean



Technical Specifications

Physical

| | |
|-------------------------|-------------------|
| Dimensions (l × w × h): | 453 × 156 × 98 mm |
| Weight: | 1.4 kg |
| Material: | Case: PC/ABS |
| Colour: | Light grey |

Functional

| | |
|-----------------|--------------------------|
| Supply voltage: | 100-240VAC/0.7A 50/60 Hz |
| Charge current: | 0.65 A |

Environmental

| | |
|-------------------------------------|---|
| Operating temperature: | +5°C to +40°C |
| Storage temperature: | -20°C to +65°C |
| Enclosure protection: | IP30, IEC EN60529 |
| Immunity to electromagnetic fields: | 3 V/m EN61000-4-3 |
| Immunity to ESD: | 4 kV contact discharge and 8 kV air discharge (EN61000-4-2) |

Recommended cables

| | |
|-------------------------|-----------------------------------|
| (not supplied by Ascom) | Power cord with IEC C13 connector |
|-------------------------|-----------------------------------|

Compliance to European regulations and standards

EU directives: 2004/108/EC(EMC)
Product marking: 
Safety: EN60950-1
EMC: EN 55022 (class B), EN61000-4-3


Compliance to US regulations and standards

Product marking: 
Safety: UL 60950-1
EMC: FCC CFR 47 Part 15

Compliance to Canadian regulations and standards

Product marking: 
Safety: CSA 60950-1
EMC: FCC CFR 47 Part 15

Compliance to Australian regulations and standards

Product marking: 
Safety: IEC 60950-1
EMC: EN 55022 (class B), EN61000-4-3

Specifications are subject to change without notice.